



Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.bondaglass.com

FEBRUARY 2019

PRODUCT DATA SHEET

Product	15 Year Paint
Type	A moisture-cured single pack polyurethane paint available in white and yellow.
Intended Use	Primarily for marine use. Suitable for wood, aluminium, fibre-glass and smooth concrete.
Special Features	The coating is tough yet flexible and has excellent adhesion. A non-yellowing/chalking paint with high UV light protection for interior and exterior use.
Preparation	Should be applied onto a bare, clean, dry substrate. Existing coatings, paint or other treatments should be removed first.
Application	Apply by brush, roller or spray.
Coats	Optimally apply 3 coats.
Drying Time	60 – 90 minutes depending on ambient conditions.
Re-coating Time	May be reapplied once surface is finger tacky. Do not attempt to recoat more than 4 hours after previous coat applied.
Application Temp.	Can be applied in poor weather conditions, high humidity and at temperatures down to freezing.
Coverage	500g/square metre.
Maintenance	Not applicable.
Compatibility	Suitable for wood, aluminium, fibre-glass and smooth concrete.
Settlement	Stir well before use.
Shelf-life/Storage	Many years if suitably stored in sealed original container. Note: product is moisture-cured, so shelf-life will be limited for opened tins.
Hazards	FLAMMABLE. Irritant. Avoid contact with eyes and skin. Wear protective gloves and eye protection. In case of contact with eyes, immediately rinse eyes with plenty of water and seek medical attention. After contact with skin, wash immediately with soap and water or a suitable skin cleanser. Keep out of reach of children. Avoid ignition sources. Do not inhale vapour. Full safety data available on request or from www.bondaglass.com
Clean-Up	Clean equipment with Rustins Cellulose Thinners. Turpentine or White Spirit are unsuitable.
Sizes	1L.