

# Automatic Extinguisher Clean Agent Gas

### FBA-G1

1 kg (1.7 m³ enclosed volume)

### FBA-G1.5

1.5 kg (2.5 m³ enclosed volume)

### FBA-G2

2 kg (3.4 m³ enclosed volume)



Flammable Liquids



Flammable Gas



Electrical Risks

Used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments. Ideal for use in sensitive locations and are a suitable option to protect high-value assets such as precious items storage, computing technology and telecommunications facilities. The unit required is determined by the gross volume of that compartment. Only one unit should be installed in any one compartment and should provide the total protection required for that compartment. The compartment should have no unnecessary ventilation that would allow needless loss of suppressant.

- CLEAN AGENT (HALON REPLACEMENT).
- ZERO OZONE DEPLETION.
- 5 YEAR WARRANTY.
- SUITABLE FOR B AND C CLASS FIRES.
- SAFE FOR USE ON ELECTRICAL EQUIPMENT.
- SUPPLIED WITH POWDER COATED, STEEL WIRE BRACKET.

Model	FBA-G1	FBA-G1.5	FBA-G2
Capacity	1 kg	1.5 kg	2 kg
Total Weight	2.14 kg	3.10 kg	3.60 kg
Total Height	330 mm	380 mm	380 mm
Total Width (incl. bracket)	95 mm	125 mm	125 mm
Working Temp.	-20° to +60°C		
Discharge Time / Temp.	Under 10 secs @ 79°C ± 5°C		
Maximum Volume Protected	1.7 m³	2.5 m³	3.4 m³
Operating Pressure	12 bar @ 20°C		
Minimum Burst Pressure	55 bar		

### FIXING INSTRUCTIONS

Mount the extinguisher with the discharge head at any angle below the horizontal.

Do not mount the extinguisher with the discharge head pointing upwards.

Do not fit extinguisher close to sources of direct heat such as exhaust manifolds or hot pipes etc.

